



S进油口, P出油口;
EIPS2-016、025油泵出油口
方向为P', 尺寸为D'

电机编码	配合油泵	A	B	C	D	L [△]	E	J	X	Y	M	N	P	Q	R	S	T	K
△ 665K05BX_SCU0EN	EIPS2-016	125.6	72.5	52.5	52.5	361.7	267	49	324	254	28.28	28.28	M6x12L	20	24.75	24.75	M6x12L	12
	EIPS2-025	144.6	82								38.89	38.89	M8x12L	26				
665K05BX_SEU0EN	EIPC3-032	153.7	83.2	57	64	361.7	267	49	324	254	30.2	58.7	M10x17L	32	22	47.5	M10x17L	18
665K08BX_SEU0EN	EIPC3-032	153.7	83.2	57	64	397.7	290	49	324	254	30.2	58.7	M10x17L	32	22	47.5	M10x17L	18
	EIPC3-040	164.7	88.7												26.2	52.4	M10x17L	20
665K10BX_SEU0EN	EIPC3-032	153.7	83.2	57	64	433.7	330	49	349	279	30.2	58.7	M10x17L	32	26.2	52.4	M10x17L	20
	EIPC3-040	164.7	88.7															
	EIPC3-050	178.7	95.7															
665K13BX_SEU0EN	EIPC3-032	153.7	83.2	57	64	469.7	372	49	349	279	30.2	58.7	M10x17L	32	26.2	52.4	M10x17L	20
	EIPC3-040	164.7	88.7															
	EIPC3-050	178.7	95.7															
	EIPC3-063	197.7	104.7															
665K16BX_SEU0EN	EIPC3-040	164.7	88.7	57	64	505.7	405	49	388	318	30.2	58.7	M10x17L	32	26.2	52.4	M10x17L	20
	EIPC3-050	178.7	95.7															
	EIPC3-063	197.7	104.7															
△ 665K16BX_SDU0EN	EIPC5-080	180.5	92.5	75	75.5	511.7	405	49	388	318	42.9	77.8	M12x20L	51	31.8	66.7	M14x24L	31.8
665K20BX_SDU0EN	EIPC5-080	180.5	92.5	75	75.5	583.7	485	55	388	318	42.9	77.8	M12x20L	51	31.8	66.7	M14x24L	31.8
	EIPC5-100	196.5	100.5															

注: 665K05、665K08电机为方便更改接线盒方向, 吊耳位置、大小均非图中所示, 具体样式以实物为准

*外形以实物为准

				編號		規格或名稱		數量	材質	V3 版本	
△	KM18F16+EIPC5-080组件规格			20201207		 宁波弘讯科技股份有限公司					
△	KM18F05增加13T规格组件及导线槽成一字结构			20200512							
記號	內容			設變編號	日期						
校核	潘浩城	20200416	比例	1/8	第3角法		圖名		KM18F花键电机+ECKERLE系	機型	
繪圖	吕素祥	20200416	單位	mm			圖號				